

Fixture Type: _____

Catalog Number: _____

Project: _____

Location: _____

Exterminator II 35W Monopoint Luminaire

System Type	Model	Beam	Color Temp & CRI	Lumens	CBCP	Finish
MO	1035	F 55°	827 2700K - 85	2476	3409	BK Black
			830 3000K - 85	2691	3700	BN Brushed Nickel
			835 3500K - 85	2815	3873	WT White
			840 4000K - 85	2828	3886	
			927 2700K - 90	2029	2824	
			930 3000K - 90	2185	3035	
		N 25°	827 2700K - 85	2487	8723	
			830 3000K - 85	2652	9279	
			835 3500K - 85	2773	9710	
			840 4000K - 85	2795	9748	
			927 2700K - 90	2020	7069	
			930 3000K - 90	2176	7517	

Example: **MO-1035F-827-BK**

DESCRIPTION

The LEDme Exterminator II offers superior light output in a compact, unobtrusive design. The Exterminator II collection was developed for upscale residential and commercial environments. Available in four high powered LED outputs, the 14W version outperforms a 20W HID, the 22W compares to a 35W HID, the 35W compares to a 50W HID, and the 52W compares to a 70W HID. For use with 120V track. Track Fixture is available in H, J/J2, and L track configurations. Order according to track layout specifications.

FEATURES

- Accommodates 1 lens accessory and 1 glare control accessory
- 365° horizontal rotation and 180° vertical aiming
- Ceiling and wall mountable
- Driver concealed within the fixture
- 5 year warranty

SPECIFICATIONS


Construction:	Die-cast aluminum with removable front cap for easy change of lenses or accessories
Power:	35W
Input:	120-277 VAC, 50/60Hz
Dimming:	ELV: 100-5%, 0-10V: 100-5%
Light Source:	Integrated LED 3 Step Mac Adam Ellipse
Lens:	Clear Tempered Glass
Rated Life:	60000 Hours
Mounting:	Can be mounted on ceiling or wall in all orientations
Finish:	Electrostatically Powder Coated Electroplated Brushed Nickel, Black, White
Operating Temp:	-4°F to 104°F (-20°C to 40°C)
Standards:	UL, cUL, Damp Location Listed, Energy Star 2.0, Title 24 JA8-2016 Compliant, Title 24:

REPLACEMENT PARTS


- SL-REF-BL18-N - REFLECTORS
- SL-REF-BL18-F - REFLECTORS



FINISHES



LINE DRAWING



Fixture Type: _____








Catalog Number: _____

Project: _____

Location: _____

Exterminator II 35W Monopoint Luminaire

ACCESSORIES

	<i>Model</i>	<i>Description</i>	<i>Finish</i>
	LENS-20-AMB LENS-20-BLU LENS-20-GRN LENS-20-RED LENS-20-YEL	<i>Colored Lens</i> <i>Colored Lens</i> <i>Colored Lens</i> <i>Colored Lens</i> <i>Colored Lens</i>	<i>Amber</i> <i>Blue</i> <i>Green</i> <i>Red</i> <i>Yellow</i>
	LENS-20-FR	<i>Clear/Frosted Lens</i>	<i>Frosted</i>
	LENS-20-SPR	<i>Spread Lens</i>	<i>Spread Lens</i>
	LENS-20-UVF	<i>UV Filter lens</i>	<i>Clear</i>
	LENS-20-BEL	<i>Beam Elongating Lens</i>	<i>Beam Elongating</i>
	LENS-20P-CRL-BK LENS-20P-CRL-BN LENS-20P-CRL-PT LENS-20P-CRL-WT	<i>Cross Louver</i> <i>Cross Louver</i> <i>Cross Louver</i> <i>Cross Louver</i>	<i>Black</i> <i>Brushed Nickel</i> <i>Platinum</i> <i>White</i>
	LENS-20-SNOOT-BK LENS-20-SNOOT-BN LENS-20-SNOOT-PT LENS-20-SNOOT-WT	<i>Snoot</i> <i>Snoot</i> <i>Snoot</i> <i>Snoot</i>	<i>Black</i> <i>Brushed Nickel</i> <i>Platinum</i> <i>White</i>