


InvisiLED® CCT

Color Temperature Adjustable Tape

WAC LIGHTING



Fixture Type:

Catalog Number:

Project:

Location:

PRODUCT DESCRIPTION

Architectural grade white tape light that delivers precise color consistency and brightness throughout the strip. 5 CCTs selectable and best-in-lighting quality make it perfect for applications like bright coves or task lighting in dry or damp locations.

FEATURES

- May be cut and easily reconnected every 4 inches
- Select and choose desirable CCT with matching CCT selectable power supply
- InvisiCoat, a UV stabilized protective coating, protects LEDs and circuitry for long term use in Damp Locations
- Equal brightness for an entire light strip
- Strong adhesive bonding with the 3M adhesive VHB
- Gold plated connector protects from corrosion, heat, and ensures a reliable connection
- 100 ft max distance between the power supply and beginning of InvisiLED®
- Closet Rated options (T24-CS1 & T24-CS2)

SPECIFICATIONS

Construction:	Flexible strip light
Cutting Interval:	4"
Input:	24VDC
Lumens:	Up to 600 lm/ft
Max Run:	Refer to ordering table
Dimming:	ELV, TRIAC, 0-10V
CRI:	95+
McAdams Steps:	2
Color Temp:	2700K / 3000K / 3500K / 4000K / 5000K
Rated Life	50,000 hours
Operating Temp:	-4°F to 104°F (-20°C to 40°C)
Standards:	UL & cUL listed, Damp Location listed, Title 24 Compliant

TAPE SELECTIONS

System	Max Run	Power	Length (in feet)					Color Temp	Finish	
T24-CS1	100+lm/ft	60ft	1.2W/ft	01	05	10	20	60	2700K	WT White
T24-CS2	200+lm/ft	40ft	2.4W/ft	01	05	10	20	40	3000K	
T24-CS3	300+lm/ft	30ft	3.0W/ft	01	05	10	20	30	3500K	
T24-CS4	400+lm/ft	20ft	4.6W/ft	01	05	10	20	N/A	4000K	
T24-CS6	600+lm/ft	15ft	6.3W/ft	01	05	10	15	N/A	5000K	










Example: **T24-CS3-10-2750WT**

waclighting.com
Phone (800) 526.2588
Fax (800) 526.2585



Headquarters/Eastern Distribution Center
44 Harbor Park Drive
Port Washington, NY 11050

Central Distribution Center
1600 Distribution Ct
Lithia Springs, GA 30122

Western Distribution Center
1750 Archibald Avenue
Ontario, CA 91760

	Model	Finish			
	T24-MM-WT	White	Tape to Tape Connector Connects tape sections		
	T24-TI-WT	White	Tape to Tape T Connector Connects tape sections		
	T24-XI-WT	White	Tape to Tape X Connector- Connects tape sections		
	T24-LI-WT	White	Tape to Tape L Connector Connects tape sections		
	T24-FF-WT	White	Joiner Cable Extender Connects joiner cable to joiner cable, female on both sides		
	T24-Y-WT T24-Y-BK	White Black	Flex Tape to Tape Y Connector Connects tape sections		
	T24-X-WT T24-X-BK	White Black	Flex Tape to Tape X Connector Connects tape sections		
	T24-IC-002 T24-IC-006 T24-IC-012 T24-IC-036 T24-IC-072 T24-IC-144 T24-IC-240	WT White BK Black	In Wall Rated Joiner Cable Connects tape sections, 2 male ends	2 in 6 in 1 ft 3 ft 6 ft 12 ft 20 ft	Example: T24-IC-002-WT
	T24-EX3-072 T24-EX3-144 T24-EX3-240 T24-EX3-1200	WT White BK Black	In Wall Rated Extension Cable Extends distance between a hard wire power supply or a wiring box to a tape section	6 ft 12 ft 20 ft 100 ft	Example: T24-EX3-072-WT

Power Supply

	Model	Input	Output	Dimming	
	PS-24DC-U60R-CS-SM PS-24DC-U96R-CS-SM	120V-277VAC	24VDC 60W 24VDC 96W	ELV / TRIAC / 0-10V	7 11/16" x 3 7/8" x 1 3/8" ≥ 0.9 pf Overload and short circuit protection Includes 6ft lead wire with connector
	PS-24DC-U288R-CSSM	120V-277VAC	24VDC 288W (3 x 96W)	ELV / TRIAC / 0-10V	10 3/4" x 8 5/8" x 1 3/8" ≥ 0.9 pf Overload and short circuit protection Includes 3 x 6ft lead wire connector