# **3" INGROUND 120V**


5032



## LANDSCAPE LIGHTING







Fixture Type:	
Catalog Numbe	r:
Project:	

#### PRODUCT DESCRIPTION

Landscape Wall Wash luminaire

#### **FEATURES**

- Adjustable beam angle
- Integral dimmer
- IP67 rated, protected from temporary immersion under water
- Drive over up to 4500lbs
- Solid diecast brass or corrosion resistant aluminum
- Available concrete pour kit
- 6' lead wire and wire nuts included
- Maintains constant lumen output against voltage drop
- UL 1598 listed
- Not suitable to use with external dimmers

### SPECIFICATIONS

Location:

 Input:
 110V - 120VAC

 Power:
 3W to 11.5W

 Brightness:
 65 lm to 515 lm

 Beam Angle:
 15° to 60°

 CRI:
 85

 Rated Life:
 45,000 hours


#### **ORDERING NUMBER**

		Color Temp		Finish	
5032	3" Inground 120V	30	3000K	BZ BBR	Bronze on Aluminum Bronze on Brass

5032-30

Example: 5032-30BBR





Typical Inground

Most light output goes into the air,
causing light pollution



Adjust Beam Angles Presets at 15°, 30°, 45°, 60°



Adjustable WAC Inground
Adjust the light to where you need it







Control Brightness Adjustable from 65lm to 515lm Presets Comparable to 10W, 25W, 35W, 50W, 75W Halogen source



Rock Guard

Protects the fixture face



5030-GRD-BZ Bronze on Aluminum

5030-GRD-BBR Bronze on Brass

Optics

Enhances saturation of florals and foliage



LENS-25-AMB

Green

LENS-25-RED Red

LENS-25-FR Frosted

Amber LENS-25-GRN

LENS-25-BLU

Blue

LENS-25-HCL

Honeycomb Louver Reduces glare

Concrete Pour Kit

For installation in concrete Five ½" NPT threaded holes, PC

5030-PIP-PVC

Shown with temporary dense foam cap



