## 


**LED Tape Light Power Supplies & Controllers** 

Responsible Lighting®



Fixture Type:	
Catalog Number:	
Project:	
Location:	

Wireless controller (accessory for wired controller) LED-TO24-WS





Class II Transfor	rmers	Model	Power	Dim	Input	Output	L	W	Н	Details
Remote	de	EN-2460D-C	60W	Yes	120V AC	24V DC 60W	6%"	35/16"	13/4"	Low Voltage Class 2 electronic DC power supply designed to be used as indoor damp location suitable power unit. Includes 6 ft lead wire.
Plug-in	109	EN-2460D-C-P	60W	Yes	120V AC	24V DC 60W	3¼"	1%"	1"	
Controllers		Model			Input	Output	L	W	Н	Details
Wired Controller		LED-TC-CTR-MSD			120V AC	24V DC	5¼"	13/8"	1¼"	4 function wired controller with master and slave options. Allows brightness control, preset color selection, or playing a rotation of color transitions with variable speed control.
Wireless Controller		LED-TO24-WS					4"	<i>2½</i> "	5/8"	Wireless remote control (for use in conjunction with wired controller), dimming for brightness, color change and change frequency. Manual control and program set up.
Signal Wire		Model	Length							Details
Signal Wire	9	LED-TC24-SW60 LED-TC24-SW120	60" 120"							Extends distance between Master Controller and Slave Controller

**WAC Lighting** www.waclighting.com Phone (800) 526.2588 • Fax (800) 526.2585

Headquarters/Eastern Distribution Center 44 Harbor Park Drive • Port Washington, NY 11050 Phone (516) 515.5000 • Fax (516) 515.5050

**Western Distribution Center** 1750 Archibald Avenue • Ontario, CA 91760 Phone (800) 526.2588 • Fax (800) 526.2585