

WAC LIGHTING

Paloma LED523 24W W Track Luminaire

| System Type & Voltage | Model | Color Temp & CRI | Lumens | CBCP | Finish |
|-----------------------|--------|------------------|--------|------|-------------|
| WTK-120 VAC | LED523 | 27 2700K - 85 | 1340 | 6840 | BK Black |
| WHK-277 VAC | | 30 3000K - 85 | 1500 | 7595 | PT Platinum |
| | | 35 3500K - 85 | 1495 | 7280 | WT White |
| | | 40 4000K - 85 | 1600 | 7650 | |
| | | 927 2700K - 90 | 1260 | 6515 | |
| | | 930 3000K - 90 | 1350 | 6635 | |

Fixture Type: _____

Catalog Number: _____

Project: _____

Location: _____

Example: **WHK-LED523-27-BK**

DESCRIPTION

Museum-quality LED luminaire with adjustable beam angle. Designed for use on W track systems (120V, 277V).

FEATURES

- Twist to adjust beam angle between 15° - 60°
- 365° horizontal rotation and 180° vertical aiming
- Driver hidden inside W track
- Integral selector to choose between independently controllable track circuits
- Comparable to 20W HID
- Driver concealed within the fixture
- 5 year warranty

SPECIFICATIONS

| | |
|------------------------|---|
| Construction: | Die-cast aluminum with cap ring. |
| Power: | 24W |
| Input: | 120 VAC, 277 VAC, 50/60Hz |
| Dimming: | ELV: 100-10% |
| Light Source: | Integrated LED 3 Step Mac Adam Ellipse |
| Rated Life: | 50000 Hours |
| Finish: | Electrostatically Powder Coated White, Platinum, Black |
| Operating Temp: | -4°F to 104°F (-20°C to 40°C) |
| Standards: | ETL, cETL, Dry Location Listed |



FINISHES



LINE DRAWING

