# Sirius

### Pendant 3000K

Fixture Type:	
Catalog Number:	
Project:	
Location:	

Model & Size	Color Temp	Finish	LED Watts	LED Lumens	Delivered Lumens
PD-81118 18"	3000K	AB Aged Brass AL Brushed Aluminum BK Brushed Black WT White	36W	2493	1217

Example: PD-81118-WT

For custom requests please contact customs@waclighting.com

### **DESCRIPTION**

Full circle. A simple glowing halo completes.

### **FEATURES**

- Up and downlight with recessed silicone diffuser
- Low profile, adjustable powered aircraft cables for an ultra-clean look
- Quick spin-on canopy design with minimal hardware for easy installation
- · Can be mounted on slope ceiling
- Driver concealed within the canopy
- 5 Year warranty

### **SPECIFICATIONS**

Color Temp: 3000K

**Input:** 120 VAC,50/60Hz

**CRI:** 90

Dimming: ELV: 100-10% ,TRIAC: 100-10%

Rated Life: 50000 Hours

Standards: ETL, cETL, Title 24 JA8 Compliant

Damp Location Listed


Construction: Aluminum body, silicone diffuser

### REPLACEMENT PARTS


HDW-SY21-CE - Hardware Pack



### **FINISHES:**



### **LINE DRAWING:**



PD-81118



# Sirius

### Pendant 3000K

Fixture Type:	
Catalog Number:	
Project:	
Location:	

Model & Size	Color Temp	Finish	LED Watts	LED Lumens	Delivered Lumens
PD-81124 24"	3000K	AB Aged Brass AL Brushed Aluminum BK Brushed Black WT White	49W	3480	1721

Example: PD-81124-WT

For custom requests please contact customs@waclighting.com

### **DESCRIPTION**

Full circle. A simple glowing halo completes.

### **FEATURES**

- Up and downlight with recessed silicone diffuser
- Low profile, adjustable powered aircraft cables for an ultra-clean look
- Quick spin-on canopy design with minimal hardware for easy installation
- · Can be mounted on slope ceiling
- Driver concealed within the canopy
- 5 Year warranty

### **SPECIFICATIONS**

Color Temp: 3000K

**Input:** 120 VAC,50/60Hz

**CRI:** 90

Dimming: ELV: 100-10% ,TRIAC: 100-10%

Rated Life: 50000 Hours

Standards: ETL, cETL, Title 24 JA8 Compliant

Damp Location Listed


**Construction:** Aluminum body, silicone diffuser

### REPLACEMENT PARTS


HDW-SY21-CE - Hardware Pack



### **FINISHES:**



### **LINE DRAWING:**





## Fixture Type:

Catalog Number:

Project:

Location:

### **Sirius**

### Pendant 3000K

Model & Size	Color Temp	Finish	LED Watts	LED Lumens	Delivered Lumens
PD-81131 31"	3000K	AB Aged Brass AL Brushed Aluminum BK Brushed Black WT White	69W	4763	2057

Example: PD-81131-WT

For custom requests please contact customs@waclighting.com

### **DESCRIPTION**

Full circle. A simple glowing halo completes.

### **FEATURES**

- Up and downlight with recessed silicone diffuser
- Low profile, adjustable powered aircraft cables for an ultra-clean look
- Quick spin-on canopy design with minimal hardware for easy installation
- · Can be mounted on slope ceiling
- Driver concealed within the canopy
- 5 Year warranty

### **SPECIFICATIONS**

Color Temp: 3000K

**Input:** 120 VAC,50/60Hz

**CRI:** 90

Dimming: ELV: 100-10% ,TRIAC: 100-10%

Rated Life: 50000 Hours

Standards: ETL, cETL, Title 24 JA8 Compliant

Damp Location Listed


Construction: Aluminum body, silicone diffuser

### REPLACEMENT PARTS


HDW-SY21-CE - Hardware Pack



### FINISHES:



### **LINE DRAWING:**



PD-81131



## **Sirius**

### Pendant 3000K

Fixture Type:	
Catalog Number:	
Project:	
Location:	

Model & Size	Color Temp	Finish	LED Watts	LED Lumens	Delivered Lumens
PD-81148 48"	3000K	AB Aged Brass AL Brushed Aluminum BK Black WT White	100 W	5330	2594

Example: PD-81148-WT

For custom requests please contact customs@waclighting.com

### **DESCRIPTION**

Full circle. A simple glowing halo completes.

### **FEATURES**

- Up and downlight with recessed silicone diffuser
- Low profile, adjustable powered aircraft cables for an ultra-clean look
- Quick spin-on canopy design with minimal hardware for easy installation
- Can be mounted on slope ceiling
- Spin-on round canopy with minimal hardware
- Driver concealed within the canopy

### **SPECIFICATIONS**

Color Temp: 3000K

**Input:** 120 VAC,50/60Hz

**CRI:** 90

Dimming: ELV: 100-10%, TRIAC: 100-10%

Rated Life: 50000 Hours


Standards: ETL, cETL, Title 24 JA8 Compliant

Damp Location Listed

**Construction:** Aluminum body, silicone diffuser



### **FINISHES:**



### **LINE DRAWING:**

